



Filter Data Sheet

Water Grade BB - Size Polypropylene Meltblown Cartridge - GWTB

- Unique & proprietary process delivers superior efficiency, life and economy
- Excellent compatibility with a wide range of chemicals
- Graded density pore structure enhances dirt holding capacity
- Easy cartridge incineration and disposal
- All polypropylene construction

Cross - Reference

Pentek®:

DGD2501 = GWTB1
 DGD5005 = GWTB5
 DGD7525 = GWTB25

GE®:

LD01 = GWTB1
 LD05 = GWTB5
 LD10 = GWTB10
 LD20 = GWTB20
 LD30 = GWTB30
 LD50 = GWTB50

Performance Specifications

Micron Ratings:

1, 3, 5, 10, 20, 25, 30, 50, 75, 100

Efficiencies: 80%

Purity

GWTB series filter cartridges are free of additives, wetting agents, binders and silicone.



Construction Materials

Filtration Media Polypropylene

Dimensions

Length 10 & 20 inches
Outside Diameter 4.5 inches
Inside Diameter 1 inches

FDA Listed Materials

Manufactured from materials which are listed for food contact applications in Title 21 of the U.S. Code of Federal Regulations.

Maximum Recommended Operating Conditions

Forward 35 PSID
Reverse 25 PSID
Change Out Differential Pressure 20 PSID
Temperature 140°F (60°C)

Liquid Flow Specifications (Based on 10" Cartridges)

Micron	GPM/PSID
1,3,5	10
10,20,25,30	12
50,75,100	15

Ordering Information

GWTB	Rating (μ)		BB	Length
Water Grade	1	3	BB = 4.5" OD	10"
	5	10		20"
	20	25		
	30	50		
	75	100		

DISCLAIMER: Filtration data presented is representative of performance observed in controlled laboratory testing. It is not given as a warranty, specification or statement of fitness for use. Specific performance can vary widely depending on contaminant type, fluid properties, flow rates and environmental conditions. It is recommended that users conduct thorough qualification testing to assure the product functions as required.