

**PERFORMANCE DATA**

**MODEL CP**

REVISED 4/2012

| PERFORMANCE DATA |                    |  |          |         |         |         |                   |
|------------------|--------------------|--|----------|---------|---------|---------|-------------------|
| MODEL NO         | DISCHARGE PRESSURE | CAPACITY- Gallons per Minute (Water at 70°F) |          |         |         |         | MOTOR HORSE POWER |
|                  |                    | PUMP SPEED                                   |          |         |         |         |                   |
|                  |                    | 1750 RPM                                     | 1150 RPM | 870 RPM | 580 RPM | 430 RPM |                   |
| CP-15            | 0                  | 1.9  | 1.3      | 1.0     | 0.7     | 0.5     | 1/2               |
|                  | 25                 | 1.7  | 1.0      | 0.5     | 0.2     | 0.1     |                   |
|                  | 50                 | 1.5  | 0.9      | 0.2     |         |         |                   |
|                  | 75                 | 1.2  | 0.8      |         |         |         |                   |
|                  | 100                | 1.0  | 0.7      |         |         |         |                   |
|                  | 125                | 0.8  | 0.5      |         |         |         |                   |
|                  | 150                | 0.6  | 0.4      |         |         |         |                   |
| CP-22            | 0                  | 4.9  | 3.2      | 2.0     | 1.6     | 1.2     | 1/2               |
|                  | 25                 | 4.1  | 2.7      | 2.0     | 1.3     | 0.9     |                   |
|                  | 50                 | 3.4  | 2.2      | 1.6     | 1.0     | 0.7     |                   |
|                  | 75                 | 2.6  | 1.7      | 1.3     | 0.8     | 0.6     |                   |
|                  | 100                | 2.0  | 1.5      | 1.0     | 0.6     | 0.4     |                   |
| CP-33            | 0                  | 9.4  | 6.0      | 4.6     | 3.1     | 2.3     | 1/2               |
|                  | 25                 | 7.0  | 4.5      | 3.4     | 2.3     | 1.7     |                   |
|                  | 50                 | 4.2  | 2.7      | 2.0     | 1.3     | 0.9     |                   |
| CP-44            | 0                  | 15.0   | 9.7      | 7.3     | 4.9     | 3.6     | 3/4               |
|                  | 25                 | 12.0   | 7.8      | 5.9     | 4.0     | 3.0     | 3/4               |
|                  | 50                 | 9.4  | 6.1      | 4.6     | 3.1     | 2.3     |                   |
| CP-56            | 0                  | 24.0   | 15.6     | 11.7    | 7.9     | 5.8     | 1 1/2             |
|                  | 25                 | 22.0   | 14.3     | 10.7    | 7.2     | 5.3     |                   |
|                  | 35                 | 20.5   | 13.3     | 10.0    | 6.7     | 4.9     |                   |
|                  | 50                 | 19.5   | 12.7     | 9.5     | 6.4     | 4.1     |                   |
| CP-67            | 0                  | 53.0   | 34.5     | 26.0    | 17.5    | 13.0    | 2                 |
|                  | 10                 | 48.0   | 31.0     | 23.4    | 15.8    | 11.7    |                   |
|                  | 20                 | 43.0   | 28.0     | 21.0    | 14.0    | 10.3    |                   |
|                  | 35                 | 34.0   | 22.0     | 16.5    | 11.0    | 8.1     | 2                 |
|                  | 50                 | 25.0   | 16.3     | 12.3    | 8.3     | 6.1     | 2                 |