



**FOR YOUR HIGH SOLID
& HEAVY LIQUID
TRANSFER DUTIES**

EXTREME SERVICE



The Total Pumping Solution

Applications

- Oil field service
- Brine and Raw water
- Sludges and slurry
- Waste oils, Tallow, etc.
- Sealant coats
- Molasses feeds
- Fertilizers
- Paper pulps

Features

- Reversible rotation and flow
- Interchangeable parts with Bowie's 3300
- Easy maintenance
- External greasing
- Latest rubber technology
- 3" pump size
Weight with flanges is approximately 142 lbs





PROCESS EQUIPMENT INC.

JH Process Equipment Inc.
 617 Jeffers Circle, Exton, PA 19341
 610-903-0900 | www.jhprocess.com

5600 Series

Pump Model	Theoretical Capacity	Maximum Speed	Maximum Flow at Maximum Speed	Maximum Temperature	Maximum Pressure	NPT Ports
------------	----------------------	---------------	-------------------------------	---------------------	------------------	-----------

5658	0.580 GPR	400 RPM	232.0 GPM (at 10 psi)	160°F	100 PSI (7 Bar)	3"
------	-----------	---------	-----------------------	-------	-----------------	----

Materials of Construction

Housing	Gears	Bearings	Shaft	Seal
---------	-------	----------	-------	------

Cast Iron	Nitrile Covered	Bronze	Steel	Packing
-----------	-----------------	--------	-------	---------

Dimensional Chart and Diagram (Inches)

